



03			
02			
01			
00			
Rev	Description	Date	APVD

Revision History

Power Supply: 24V AC

N.F.B: No Fuse Breaker
P.E: Protective Earth
H: Heater
HT: Heater Thermostat
MT: Motor Thermostat
M: Motor
S1: Switch
LS1: Limit Switch for OPEN (5A/250V AC)
LS2: Limit Switch for CLOSE (5A/250V AC)
LS3: SPDT Auxiliary Limit Switch (5A/250V AC)
LS4: SPDT Auxiliary Limit Switch (5A/250V AC)

- Notes:
- 1) "N" connects to 1, "L" connects to 7.
 - 2) S1 comes On for "OPEN".
 - 3) S1 comes Off for "CLOSE".
 - 4) Wiring is shown with Actuator Fully Closed.
 - 5) **Applicable to Actuator models iVS-A, B, C, D.**

Fully Open	A to C
Fully Close	D to F

Innovative Actuation Incorporated
1-215 Traders Blvd. Mississauga, Ontario Canada www.ivact.com

DESCRIPTION:
24V AC TWO POSITION with Heater,
Thermostat and Auxiliary Switches 50% Duty

WIRING DIAGRAM CODE:	SA	DATE:	APR. 21/2018
WIRING DIAGRAM NO.:	S-1AN21NNN-1		