



03			
02			
01			
00			
Rev	Description	Date	APVD

**Revision History**

Power Supply: 24V DC

N.F.B: No Fuse Breaker  
P.E: Protective Earth  
H: Heater  
HT: Heater Thermostat  
MT: Motor Thermostat  
M: Motor  
S1: Switch  
LS1: Limit Switch for OPEN (5A/250V AC)  
LS2: Limit Switch for CLOSE (5A/250V AC)  
LS3: SPDT Auxiliary Limit Switch (5A/250V AC)  
LS4: SPDT Auxiliary Limit Switch (5A/250V AC)

- Notes:
- 1) "+" connects to 1, "-" connects to 7.
  - 2) S1 comes On for "OPEN".
  - 3) S1 comes Off for "CLOSE".
  - 4) Wiring is shown with Actuator Fully Closed.
  - 5) **Applicable to Actuator models iVS-A, B, C, D.**

Fully Open	A to C
Fully Close	D to F

**Innovative Actuation Incorporated**  
1-215 Traders Blvd. Mississauga, Ontario Canada www.ivact.com

**DESCRIPTION:**  
24V DC TWO POSITION with Heater,  
Thermostat and Auxiliary Switches 50% Duty

WIRING DIAGRAM CODE: SA DATE: APR. 21/2018

WIRING DIAGRAM NO.: S-1AN21NNN-2

**POSITIVE SWITCHING**

**ACTUATOR**