



03			
02			
01			
00			
Rev	Description	Date	APVD

Revision History

Power Supply: 24V AC or DC

P.E: Protective Earth
H: Heater
HT: Heater Thermostat
MT: Motor Thermostat
M: Motor
LS1: Limit Switch for OPEN (3A/250V AC)
LS2: Limit Switch for CLOSE (3A/250V AC)
LS3: SPDT Auxiliary Limit Switch (3A/250V AC)
LS4: SPDT Auxiliary Limit Switch (3A/250V AC)

- Notes:
- 1) Modulating Board
Input Signal : 4-20mA, 2-10V
(It is suggested to use the shielding wire and its length should not exceed 30m.)
Output Signal : 4-20mA, 2-10V
 - 2) Wiring is shown with Actuator Fully Closed.
 - 3) **Applicable to Actuator models iVQ-C, D.**



Innovative Actuation Incorporated

1-215 Traders Blvd. Mississauga, Ontario Canada www.ivact.com

DESCRIPTION:
24V AC/DC Modulating with Heater, Thermostat,
Auxiliary Switches and 4-20mA Feedback
75% Duty

WIRING DIAGRAM CODE: **QM** DATE: **JAN. 08/2021**

WIRING DIAGRAM NO.: **Q-1FN21N3N-1**